


# view@x

## Premium Core Alignment Fusion Splicer

- Ultrafast Splicing & Heating
- Large Battery Capacity
- Bright Operation Lighting
- Versatile Fiber Holder
- Quick & Intuitive Interface



-  Real-Time Tracking
-  Report & Data Management
-  Job & Work Management
-  Device Management



## TECHNICAL SPECIFICATIONS

Items	Specifications
Model	VIEW 8X
Alignment Method	Core Alignment
Number of Fibers	Single
Applicable Fibers	SM (ITU-T G.652&T G.657) / MM (ITU-T G.651) / DS (ITU-T G.653) / NZDS (ITU-T G.655) / CS (G.654) / EDF / BIF
Coating Diameter	100µm - 3mm
Cladding Diameter	80 - 150µm
Cleave Length	5 - 16mm
Typical Splice Loss	SM: 0.01dB / MM: 0.01dB / DS: 0.03dB / NZDS: 0.03dB / G.657: 0.01dB
Return Loss	>> 60dB
Splice Time	Quick mode: Avg. 4 sec / SM mode: Avg. 5 sec / Auto mode: Avg. 7 sec
Splice Programs	Max 128 modes
Automatic Calibration	Automatic Arc Calibration by air pressure & temperature
Electrode Life span	6000 Arc Discharges
Heating Programs	Max 32 modes
Heating Time	Quick: 9s / Average: 13s
Protection Sleeve	20mm - 60mm
Data Output	Cloud (View Pro Manager) + USB-C
Splice Memory	20,000 Splice data / 10,000 Splice image
Battery	Battery Capacity: 9000mAh / Operation Cycle: 500 cycles (Splicing + Heating)
Power Supply	AC Input 100 - 240V, DC Input 9 - 19V
Monitor	5.0" Color LCD display, Full Touch Screen
Magnification	x360, x520
Size	162 x 143 x 158mm
Weight	2.68kg
Pull Test	1.96 - 2.25N

\*Splicing Time: Measured from the time of fibers entering the screen until the estimated loss is displayed. Splicing time can vary depending on the calibration status.

\*Battery: Measured as 1-minute cycle of splicing and heating. Measured in Power Save mode.

## WEIGHT AND DIMENSIONS



## ENVIRONMENTAL CONDITION & TEST

Items	Specifications
Operating Conditions	Altitude: 0 - 5000m Humidity: 0 - 95%, non-dew Temperature: -10 - 50°C Wind: up to 15m/sec
Storage Conditions	Humidity: 0 - 95%, non-dew Temperature: -40 - 80°C
Resistance Tests	Shock Resistance : 76cm for bottom surface drop Exposure to Dust : 0.1 to 500um diameter aluminium silicate Rain Resistance : 10 mm/h for 10 mins

- Water resistance (IPx2)
- Shock resistance (Drop from 76cm)
- Dust resistance (IP5X)



Water  
Resistance



Shock  
Resistance



Dust  
Resistance

The Information on this catalog is subject to change without prior notice.

**i** INNO Instrument does not accept responsibility for damages arising from misuse of the product.